

DOCKET NO. RFSC-0004

2862

PATENT

#4

RWB

4-6-04

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

Clinton Hartmann

Serial No.: 10/062,791

TC 2800 MAILING ROOM

FEB 26 2003

RECEIVED FOR  
EXAMINATION


Filed: January 30, 2002

For: "OBJECT-NAMING NETWORK INFRASTRUCTURE FOR  
IDENTIFICATION TAGS AND METHOD OF OPERATION THEREOF"

Group: 2862

Examiner: N/A

Commissioner for Patents  
Washington, D. C. 20231



Sir:

LETTER TO OFFICIAL DRAFTSMAN

Transmitted herewith are thirteen sheets of formal drawings to be substituted for the informal drawings initially filed in the above-identified application for patent.

Respectfully submitted,

HITT GAINES & BOISBRUN, P.C.

Jimmy L. Heisz  
Registration No. 38,914

Date: Feb 19, 2003

P.O. Box 832570  
Richardson, Texas 75083  
(972) 480-8800

RECEIVED  
DEC 31 2003  
GROUP 3600



1/13




FIG.1



2/13




FIG.2



3/13






FIG.3



FIG.4






FIG.5



FIG. 6






FIG. 7B





FIG. 7A



713



FIG. 8








FIG. 9



10/13

THREE REFLECTORS WITH MINIMUM SPACING OF 5 SLOTS HAVE 286 POSSIBLE PLACEMENTS IN 21 SLOTS  
EACH ROW SHOWS A UNIQUE PLACEMENT OF 2 ITEMS (X&Y) AND MULTIPLE PLACEMENT FOR THE 3RD (Z)

FIG. 10



11/13

IN 10 SLOTS, TWO REFLECTORS WITH MINIMUM SPACING OF 2 SLOTS HAVE 36 POSSIBLE PLACEMENTS

STATE	0	1	2	3	4	5	6	7	8	9
0	X		Y							
1	X			Y						
2	X				Y					
3	X					Y				
4	X						Y			
5	X							Y		
6	X								Y	
7	X									Y
8		X		Y						
9		X			Y					
10		X				Y				
11		X					Y			
12		X						Y		
13		X							Y	
14		X								Y
15			X		Y					
16			X			Y				
17			X				Y			
18			X					Y		
19			X						Y	
20			X							Y
21				X		Y				
22				X			Y			
23				X				Y		
24				X					Y	
25				X						Y
26					X		Y			
27					X			Y		
28					X				Y	
29					X					Y
30						X		Y		
31						X			Y	
32						X				Y
33							X		Y	
34							X			Y
35								X		Y

FIG.11



**12/13**

IN 10 SLOTS, TWO REFLECTORS WITH MINIMUM SPACING OF 3 SLOTS AND ALLOWING  
ONLY ONE EVEN NUMBERED AND ONE NUMBERED SLOT PROVIDES 16 POSSIBLE STATES

STATE	0	1	2	3	4	5	6	7	8	9
0	X			Y						
1	X				Y					
2	X					Y				
3	X								Y	
4		X		Y						
5	X					Y				
6	X						Y			
7			X		Y					
8		X				Y				
9		X							Y	
10			X		Y					
11			X				Y			
12				X		Y				
13				X					Y	
14					X			Y		
15						X			Y	

**FIG.12**



13/13




FIG.13

